

NASA/TM-2009-215950



# A Multidisciplinary Tool for Systems Analysis of Planetary Entry, Descent, and Landing (SAPE)

*Jamshid A. Samareh*  
*Langley Research Center, Hampton, Virginia*

---

November 2009

## NASA STI Program . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA scientific and technical information (STI) program plays a key part in helping NASA maintain this important role.

The NASA STI program operates under the auspices of the Agency Chief Information Officer. It collects, organizes, provides for archiving, and disseminates NASA's STI. The NASA STI program provides access to the NASA Aeronautics and Space Database and its public interface, the NASA Technical Report Server, thus providing one of the largest collections of aeronautical and space science STI in the world. Results are published in both non-NASA channels and by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
  - **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
  - **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.
  - **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.
  - **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
  - **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.
- Specialized services also include creating custom thesauri, building customized databases, and organizing and publishing research results.
- For more information about the NASA STI program, see the following:
- Access the NASA STI program home page at <http://www.sti.nasa.gov>
  - E-mail your question via the Internet to [help@sti.nasa.gov](mailto:help@sti.nasa.gov)
  - Fax your question to the NASA STI Help Desk at 443-757-5803
  - Phone the NASA STI Help Desk at 443-757-5802
  - Write to:  
NASA STI Help Desk  
NASA Center for AeroSpace Information  
7115 Standard Drive  
Hanover, MD 21076-1320

NASA/TM-2009-215950



# A Multidisciplinary Tool for Systems Analysis of Planetary Entry, Descent, and Landing (SAPE)

*Jamshid A. Samareh*  
*Langley Research Center, Hampton, Virginia*

National Aeronautics and  
Space Administration

Langley Research Center  
Hampton, Virginia 23681-2199

---

November 2009

The use of trademarks or names of manufacturers in this report is for accurate reporting and does not constitute an official endorsement, either expressed or implied, of such products or manufacturers by the National Aeronautics and Space Administration.

Available from:

NASA Center for AeroSpace Information  
7115 Standard Drive  
Hanover, MD 21076-1320  
443-757-5802

## Abstract

SAPE is a Python<sup>®</sup>-based multidisciplinary analysis tool for systems analysis of planetary entry, descent, and landing (EDL) for Venus, Earth, Mars, Jupiter, Saturn, Uranus, Neptune, and Titan. The purpose of SAPE is to provide a variable-fidelity capability for conceptual and preliminary analysis within the same framework. SAPE includes the following analysis modules: geometry, trajectory, aerodynamics, aerothermal, thermal protection system, and structural sizing. SAPE uses the Python language—a platform-independent open-source software—for integration and for the user interface. The development has relied heavily on the object-oriented programming capabilities that are available in Python. Modules are provided to interface with commercial and government off-the-shelf software components (e.g., thermal protection systems and finite-element analysis). SAPE runs on Microsoft<sup>®</sup> Windows<sup>®</sup> and Apple<sup>®</sup> Mac<sup>®</sup> OS X and has been partially tested on Linux<sup>®</sup>.

## Nomenclature

$c$	=	gas mass fraction
$C_D$	=	drag coefficient
$C_H$	=	heat transfer coefficient
$C_p$	=	pressure coefficient
$D$	=	drag, N
$g$	=	gravity, m/s <sup>2</sup>
$h$	=	height above planet, m
$H$	=	ellipsled height, m
$K$	=	heating constant
$L$	=	lift, N
$m$	=	mass, kg
$M$	=	molecular mass
$q$	=	stagnation-point heating rate, W/m <sup>2</sup>
$r$	=	radius, m
$R$	=	body radius, m
$s$	=	distance downrange, m
$t$	=	time, s
$u$	=	velocity, m/s
$V$	=	velocity, m/s
$W$	=	ellipsled width, m
$\beta$	=	backshell half-cone angle, deg
$\theta$	=	forward shell half-cone angle, deg
$\gamma$	=	flight path angle, deg
$\rho$	=	density, kg/m <sup>3</sup>

## Subscripts

$b$	=	base
$c$	=	convective heating
$e$	=	boundary layer edge
$n$	=	nose
$p$	=	planet
$r$	=	radiative heating
$s$	=	probe shoulder

## I. Introduction

Systems analysis of a planetary entry, descent, and landing (EDL) is a multidisciplinary activity in nature. The purpose of the analysis is to gain a better understanding of various entry system concepts and their limitations. Systems analysis teams typically include one or more systems engineers and discipline-specific experts in flight mechanics, aerodynamics, aerothermodynamics, structural analysis, and thermal protection systems (TPS). Other discipline experts, for example, propulsion experts, are consulted as needed. The systems analysis process may take from several weeks to several years (references 1 and 2 provide a good summary of typical systems analysis activities). Integrated tools, like SAPE, improve the performance of the systems-analysis team by automating and streamlining the process, and this improvement can reduce the errors that stem from manual data transfer among discipline experts. The role of discipline experts in the systems-analysis process is indispensable and cannot be replaced by any tool.

Several efforts have been made to develop integrated tools with a focus on different aspects of planetary EDL. For example, the integrated design systems<sup>3</sup> (IDS) initiative developed an integrated tool by using a common gateway interface (CGI) to integrate codes for various disciplines from a distributed network. The IDS program used the Perl script for integration. Allen et al.<sup>4</sup> provide more details on the IDS design and implementation. The Hyperprobe program<sup>5</sup> is another IDS-like Web-based implementation, with the addition of a relational database management system. Unlike IDS and Hyperprobe, the Planetary Entry Systems Synthesis Tool<sup>6</sup> (PESST) is based on Matlab<sup>®</sup>.\*

The key goals for SAPE development are:

- 1) Perform EDL systems analysis for any planetary body with an atmosphere.
- 2) Operate cross-platform (i.e., Windows, Mac, and Linux operating systems).
- 3) Use existing software components.
- 4) Use open-source software to avoid software licensing issues.
- 5) Perform low-fidelity systems analysis in one hour on a computer that is comparable to an average laptop.
- 6) Keep discipline experts in the analysis loop.

The next section discusses the use of the Python language for tool integration. Section III presents the design structure matrix for planetary EDL analysis. Section IV reviews the eight planetary bodies with atmospheres. Sections V through X introduce the six major modules that are included in SAPE. The last section presents recommendations for future enhancements.

The next section discusses the use of the Python language for tool integration. Section III presents the design structure matrix for planetary EDL analysis. Section IV reviews the eight planetary bodies with atmospheres. Sections V through X introduce the six major modules that are included in SAPE. The last section presents recommendations for future enhancements.

## II. Use of Python for Integration Environment

SAPE uses the Python<sup>†</sup> language to develop and integrate various modules. Python is a free, object-oriented, high-level programming language that is often used as a scripting language. Python is open source and is supported by a large community and managed by the Python Software Foundation. Python is available for most computer platforms and has a large number of standard libraries, which range from scientific to Web applications. Python users include

\* <http://www.mathworks.com>

† <http://www.python.org>

Google<sup>™</sup>, Yahoo<sup>®</sup>, YouTube<sup>™</sup>, Disney, the New York Stock Exchange, the European Organization for Nuclear Research (CERN), and many other large commercial entities. The United Space Alliance has used Python to streamline space shuttle-mission design.\*

### III. EDL Design Structure Matrix (DSM)

The multidisciplinary EDL problem can be decomposed into a set of key disciplines. These discipline areas, modules, can be represented in matrix form using the DSM approach. The matrix is a graphical approach for representing the interdependencies among these various modules. The DSM is a square matrix with the analysis modules positioned along a main diagonal. Table 1 shows a typical DSM representation for the integrated EDL analysis. For each analysis module shown on the DSM diagonal, relevant outputs are listed in the corresponding row; the inputs are listed in the corresponding column. For example, the required inputs for structural analysis are the outer mold line (OML), mass distribution, and loads. Structural analysis outputs include an estimate for the structural mass as well as displacements. DSM analysis tools, such as DeMAID,<sup>7</sup> can be used to analyze the DSM and identify the critical dependencies.

The EDL integrated analysis process is a complex system, and SAPE currently includes only the six most important disciplines: geometry, trajectory, aerodynamics, aerothermodynamics, TPS, and structural sizing.

### IV. Planetary Bodies with Atmosphere

Eight planetary bodies in our solar system have an appreciable atmosphere; these are Venus, Earth, Mars, Jupiter, Saturn, Uranus, Neptune, and Titan. The data that are included in SAPE for all eight planetary bodies are based on the NASA Goddard Planetary Fact Sheet<sup>†</sup> (see table 2). These bodies can be divided further into small bodies (Venus, Earth, Mars, and Titan) and large gas giants (Jupiter, Saturn, Uranus, and Neptune). Planetary entry characteristics<sup>8</sup> for each body are listed in table 3.

SAPE users can either use the nominal atmospheric profiles<sup>9</sup> that are built into SAPE or provide the atmospheric profile in a tabular form. Details on the nominal atmospheric profiles are available for Earth, Mars, Neptune, Titan, and Venus in Justus et al.<sup>10</sup> and for Jupiter, Neptune, Saturn, and Uranus in Justus et al.<sup>11</sup> (see figure 1.)

\* <http://www.python.org/about/success/usa> (last visited on February 09, 2009)

† <http://nssdc.gsfc.nasa.gov/planetary/factsheet/index.html> (last visited on February 05, 2009)

Table 1. Design Structure Matrix for EDL Analysis

	Optimization module	Database module	Geometry module	Pack'g & mass pro	Trajectory analysis	Propulsion analysis	Aero analysis	Aerothermal analysis	TPS sizing	Structural analysis	Stability and control	Cost analysis	Reliability analysis
Optimization module	<b>Optimization module</b>	Design variables											
Database module	Obj & const.	<b>Database module</b>	Geometry variables	Design variables	Design variables	Design variables	Design variables	Design variables	Design variables	Design variables	Design variables	Design variables	Design variables
Geometry module		TBD	<b>Geometry module</b>	OML	Parameters	Flow path	OML	OML	OML	OML	Dimensions		
Pack'g & mass pro		Weight breakdown		<b>Pack'g &amp; mass pro</b>	Dry mass					Mass distribution	Mass, C.G., & inertias		
Trajectory analysis		Trajectory profile		Fuel weight	<b>Trajectory analysis</b>	Flight conditions	Flight conditions	Flight conditions	G-load	Inertia loads			
Propulsion analysis		TBD		Propulsion weight	TSFC	<b>Propulsion analysis</b>	Propulsion environment	Propulsion heating		Propulsion loads	Propulsion loads		
Aerodynamics analysis		TBD			Integrated aero	Aero environment	<b>Aero analysis</b>	Pressure distribution	Aero load	Distributed loads	Integrated aero		
Aerothermal analysis		TBD			Heating corrections			<b>Aerothermal analysis</b>	Thermal environment	Temperature distribution			
TPS Sizing		TBD		TPS weight					<b>TPS Sizing</b>	TPS Size			
Structural analysis		TBD		Structural weight			Structural displacements		Sizing data	<b>Structural analysis</b>			
Stability and Control		Control margins									<b>Stability and control</b>		
Cost analysis		Cost										<b>Cost analysis</b>	
Reliability analysis		Reliability index											<b>Reliability analysis</b>

Columns are inputs, and Rows are outputs



Table 2. Planetary Body Characteristics

Planets	Earth	Mars	Titan	Venus	Neptune	Jupiter	Saturn	Uranus
Radius, km	6378	3397	2575	6052	24764	71492	60268	25559
Gravity, m/s <sup>2</sup>	9.8	3.7	1.35	8.9	11	23.1	9	8.7
Surface atmo. $\rho$ kg	1.22	0.02	1.55	65	0.45*	0.16*	0.19*	0.42*
Atmo. height, km	8.5	11.1	10	15.9	20	27	59.5	27.7
Atmo. interface, km	120**	120**	800**	130**	630**	395	750	555
Atmo. mole. wt.	28.870	43.501	28.269	43.450	2.373	2.219	2.081	2.271

\* at one bar

\*\* based on refs. 9-11 at  $10^{-9} < \rho < 10^{-8}$

Table 3. Planetary Entry Characteristics

	Composition	Entry speeds	Heat rates and loads
Small planets: Venus, Earth, Mars, Titan	CO <sub>2</sub> , N <sub>2</sub> , O <sub>2</sub>	5–12 km/sec	10's to 100's W/cm <sup>2</sup> 10 <sup>3</sup> –10 <sup>4</sup> J/cm <sup>2</sup>
Gas giant planets: Jupiter, Saturn, Uranus, Neptune	H <sub>2</sub> , He	25–60 km/sec	1000's W/cm <sup>2</sup> 10 <sup>5</sup> –10 <sup>6</sup> J/cm <sup>2</sup>




Figure 1. Nominal atmospheric profiles.<sup>10-11</sup>

## V. Geometry Module

The geometry module is written entirely as an object in Python, and three types of geometries can be created: sphere-cone probes, tori, and asymmetric ellipsoids.

SAPE can model most existing sphere-cone probes (See appendix A.) The creation of sphere-cone probe geometry uses five flags and a set of geometry parameters. The flags are used to define various probe sections: spherical nose (0, 1), conical forward section (0, 1), shoulder fillet (0, 1), aft-body conical section (0, n), and back-end section (1). The numbers in parentheses indicate the possible number of individual sections. The possible back-end shapes are flat, spherical cap, ellipsoid cap, and fillet. Figure 2(a) shows a sample sphere-cone model, which consists of a spherical nose, a conical forward section, a shoulder fillet, three aft-conical sections, and a flat backend (flags: 1, 1, 1, 3, and flat). Additional information and figures on sphere-cone geometry models are given in appendix A.

The ellipsled is an elliptically blunted cylinder that was originally proposed by Muth et al.<sup>12</sup> for an Earth-return aerocapture application. Edquist et al.<sup>13</sup> present a modified version of the ellipsled in which the nose is defined by two ellipsoids with different minor axes. The modified ellipsled is defined by five parameters (figure 2(b)): total length, nose length, width, height, and offset ratio. The geometry module can also generate tori, which are donut-like shapes that are defined by major and minor radii (figure 2(c)).




Figure 2. Available geometry shapes and parameters.

## VI. Aerodynamics

SAPE currently includes two aerodynamic models: an analytical expression for aerodynamic drag at a zero angle of attack and DACFREE code. The analytical expression for the drag of a sphere cone<sup>14</sup>

$$C_D = C_{p_{\max}} \left[ \sin^2 \theta + \frac{R_n}{2R_b} (1 - 2 \sin^2 \theta \cos^2 \theta - 4 \sin^4 \theta) \right] \quad (1)$$

The DACFREE<sup>15</sup> code has been used in many planetary entry studies and uses standard free-molecular and modified Newtonian methods. The geometry that is input is a set of triangles with appropriate boundary conditions. Python was used to wrap the DACFREE code and integrate it into SAPE. Figures 3 shows comparisons of integrated DACFREE results with those of Moss et al.<sup>16</sup> (top), Moss et al.<sup>17</sup> (center), and Edquist et al.<sup>13</sup> (bottom).

## VII. Aerothermodynamics

SAPE currently includes a simple analytical expression for stagnation-point heating. However, the plan is to include the Langley Approximate Three-Dimensional Convective Heating (LATCH) code<sup>18</sup>, which is an approximate three-dimensional heating code that is based on the axisymmetric analog for general three-dimensional boundary layers.


SAPE currently uses the analytical expression for stagnation heating rate that was developed by Sutton and Graves<sup>19</sup>:

$$q = KV^3 \sqrt{\frac{\rho}{R_n}} \quad (2)$$


where  $V$  is the velocity,  $\rho$  is the atmospheric density, and  $R_n$  is the nose radius. What makes Sutton and Graves's analytical expression unique is that the constant  $K$  is derived for a general gas mixture. The coefficient  $K$  is a function of the atmospheric mass fractions, the molecular weights, and their individual transport properties. Sutton and Graves provide two expressions for  $K$ :

$$K = \frac{0.1106}{\sqrt{\sum \frac{c_i}{M_i \gamma_i}}}, \quad K = \frac{1}{\sqrt{\sum \frac{c_i}{K_i^2}}} \quad (3)$$


where  $c_i$  are the mass fractions. The parameters  $\gamma_i$  that are used in Eq. (3) are the transport parameters of the base gas of a mixture and should not be confused with the flight-path angle that is used in the trajectory section (other constants are presented in table 4).



(a) Microprobe (reference 16).



(b) Pathfinder (reference 17).



(c) Ellipsled (reference 13).

Figure 3. Comparisons of DACFREE results with those in references 13, 16, 17.

Table 4. Constant K

Coeff. for equation			Mass fractions							
	$M_i$	$K_i$	Earth	Mars	Titan	Venus	Neptune	Jupiter	Saturn	Uranus
$N_2$	28.013	0.11	0.785	0.027	0.984	0.035				
$O_2$	31.999	0.12	0.215	0.001						
$H_2$	2.016	0.04					0.8	0.898	0.967	0.825
$He$	4.003	0.08					0.19	0.102	0.033	0.152
$Ne$	20.180	0.15								
$Ar$	39.948	0.15		0.016						
$CO_2$	44.010	0.12		0.956	0.016	0.965				
$NH_3$	17.031	0.1					0.01			0.023
$CH_4$	16.042	0.08								
$K \cdot 10^{-4}$ (eq. 1)			1.7623	1.8980	1.7407	1.8960	0.6719	0.6556	0.6356	0.6645

Tauber and Sutton<sup>20</sup> present a simple procedure to approximate the radiative heating for Earth and Mars. Both the Sutton/Graves and the Tauber/Sutton procedures provide only approximations and should be corrected with available higher fidelity numerical solutions and experimental results.

The plan is to include TSAAPE<sup>21</sup>, which is a script that is tailored to perform aeroheating analysis for sphere cones using LAURA<sup>22</sup> computer code. The script currently supports Earth, Mars, Titan, Venus, Saturn, and Neptune.

## VIII. Trajectory

SAPE includes a simple trajectory code. Work is underway to include POST-2,<sup>23</sup> which is a more sophisticated trajectory code. The simple trajectory code is based on equations for planar flight,<sup>24</sup> as shown in figure 4.

$$\begin{aligned}
 \frac{dV}{dt} &= -\frac{D}{m} - g \sin \gamma, & \frac{V d\gamma}{dt} &= \frac{L}{m} - \left(g - \frac{V^2}{r}\right) \cos \gamma, \\
 \frac{ds}{dt} &= \frac{R_p}{r} V \cos \gamma, & \frac{dr}{dt} &= \frac{dh}{dt} = V \sin \gamma,
 \end{aligned} \tag{4}$$

where  $g = g_s \left( \frac{R_p}{R_p + r} \right)^2$ .

Readers should consult Griffin and French<sup>24</sup> for additional information. The above equation set is a system of first-order differential equations with its initial values— $V$ ,  $h$ , and  $\gamma$ —defined at atmospheric entry.




Figure 4. Planar flight.

SAPE uses the Cash and Karp Runge-Kutta method with the adaptive step size<sup>25</sup>. This particular method is fifth-order accurate and more efficient by a factor of two than standard step-doubling methods. The method accuracy is controlled by defining a maximum error, and the method adjusts the time step to the user-defined level of accuracy. Users also can force a minimum time step to create a larger number of data points along the trajectory. A simple, one-dimensional minimization algorithm based on Ridder's<sup>25</sup> approach is included for the aerocapture applications. The Ridder algorithm is a variation of the false-position root finding approach with superlinear convergence property.

The trajectory code implementation is in C++ for efficiency, and the code was verified against several test cases. Figure 5 shows a comparison of the results from the simple trajectory code with those of POST-2,<sup>23</sup> and the results are in excellent agreement.

The second set of test cases was based on the aerocapture study of Hall and Lee,<sup>26</sup> in which shallow and steep entries into four planetary bodies (Mars, Neptune, Titan, and Venus) were analyzed. Table 5 compares the results from SAPE trajectory with those from Hall and Lee, and the results are in good agreement.




Figure 5. Comparison with POST (symbols).

Table 5. Comparison SAPE Results with Results of Hall and Lee

	Peak ballute temperature (K)		
	Hall et al.	Current	% Error
Titan (shallow)	1030.0	1033	0.28
Titan (steep)	1073.0	1077	0.36
Neptune (shallow)	1257.0	1293	2.83
Neptune (steep)	1369.0	1369	0.00
Venus (shallow)	908.0	901	0.77
Venus (steep)	974.0	967	0.73
Mars (shallow)	805.0	804	0.15
Mars (steep)	868.0	866	0.22

## IX. Thermal Protection System (TPS)

SAPE currently provides an interface to the TPS sizing code FIAT<sup>27</sup>. The actual FIAT code is not part of SAPE and should be obtained directly from NASA Ames Research Center. Necessary inputs to FIAT includes the recovery enthalpy  $H_r$ , the heat flux term  $\rho_e u_e C_H$ , pressure  $p$ , and radiative heat flux  $q_r$ . Trajectory and aerothermal modules generate the free stream density  $\rho_\infty$ , velocity  $V_\infty$ , convective heat flux  $q_c$ , and radiative heat flux  $q_r$  variables. Figure 6 shows a sample TPS result, which is for a Stardust-class vehicle with a ballistic coefficient of  $60 \text{ kg/m}^2$ , an  $L/D$  of 0.2, an entry velocity of  $12 \text{ km/s}$ , and a flight-path angle of  $-10^\circ$ . The heat rate includes a margin of 30%. Figure 6(a) shows the resulting heat rates and the total heat load, and figure 6(b) shows the back wall temperature and the recession rate for Phenolic Impregnated Carbon Ablator (PICA) concept. FIAT calculated the optimal thickness to be 2.8 cm.




Figure 6. Heating and TPS sample results for a Stardust-class probe.

## X. Finite-Element Analysis and Sizing

SAPE is capable of analyzing and sizing certain classes of planetary probes. Automating the generation and the analysis of the finite-element model (FEM) are quite challenging. These tasks can be simplified by restricting the analysis to sphere-cone shapes. The current FEM topology that is used in SAPE is based on the existing structural topology, which consists of the shell, the external support structure, and the internal payload support. Figure 7 shows various structural topologies for a generic probe.




Figure 7. Sample structural topologies for Pathfinder class probe.

After generating the FEM, finite-element analysis (FEA) codes are used to automatically size the vehicle. The FEA code provides estimates for the structural mass for given launch and entry loads. Figure 8 shows the von Mises stresses on a typical aeroshell structural model.




Figure 8. Sample FEA result.



## **XI. Summary**

SAPE is a Python-based multidisciplinary analysis tool that has been developed for systems analysis for planetary entry, descent, and landing (EDL) for Venus, Earth, Mars, Jupiter, Saturn, Uranus, Neptune, and Titan. SAPE includes the following analysis modules: geometry, trajectory, aerodynamics, aerothermal, thermal protection system, and structural sizing. The geometry module can model most existing sphere-cone probes, ellipsoids, and tori. The aerodynamic module includes an analytical expression for drag and DACFREE code. The aerothermal module is based on Sutton-Graves approximation, and the plan is to include the Langley Approximate Three-Dimensional Convective Heating (LATCH) code. SAPE includes a simple trajectory code, which is based on equations for planar flight. The work is underway to include POST-2. SAPE currently provides an interface to the TPS sizing code FIAT. SAPE is capable of analyzing and sizing certain classes of planetary probes. The current FEM topology that is used in SAPE is based on the existing sphere-cone structural topology, which consists of the shell, the external support structure, and the internal payload support. SAPE modules have been validated against existing tools; however, the integrated system has not been fully validated yet. One major short-term goal is to verify the current integrated system. The medium-term goals are to


1. Integrate an updated version of the FEA script discussed in section X.
2. Integrate POST-2.
3. Include sensitivity analysis capability.
4. Include system-based Monte Carlo simulation capability.
5. Include LATCH and TSAAPE codes.

## **XII. Acknowledgement**

The author would like to acknowledge Jim Hoffman for his work on FEM generation, Alireza Mazaheri for developing TSAAPE, Aaron Olds for developing scripts for POST-2, and Erik Tyler for his help with FEM sizing (all from Analytical Mechanics Associates, Inc.).

## Appendix A: Possible Sphere-Cone Shapes

Figure A1 shows the existing sphere-cone probes that are presented by Davies and Arcadi.<sup>28</sup> The numbers that are shown below the name of each probe are the SAPE geometry flags, as used in figure 2(a). Table A1 shows geometry parameters for shape shown in figure A1.



**Figure A1. Existing sphere-cone probes.**

(s) spherical nose, (c) conical section, and (f) fillet

Table A1. Geometry Parameters for Existing Planetary Probes

	$r_b$	$L/r_b$	$r_n/r_b$	$r_s/r_b$	$\alpha$	$\beta$	<i>Backshell Conic Length Ratios</i>	<i>Backend Shapes</i>
ARD	1.4	1.457	2.4	0.1	0	33, 90, 0	0.75, -0.31, 0.25	Flat
Apollo	1.955	1.85166	2.4	0.1	0	33	1	Fillet
Beagle	0.45	1.11	0.93	0.0644	70	47, 47	0.5, 0.5	Flat
Fire-II	0.336	1.564	2.78	0	0	90, 0, 90, 33	0.04, .11, -0.04, 0.89	Flat
Galileo_Probe	0.63	1.47	0.35	0	44.86	0, 60, 0	0.07, 0.07, 0.07	Ellipsoid
Genesis	0.75	1.267	0.57	0.044	60	20, 60	0.5, 0.5	Flat
HAYABUSA	0.202	1	1	0	45	45, 90, 45	0.79, -0.06, 0.21	Flat
Huygens	1.35	0.73	0.926	0	60	90	-0.6	Ellipsoid
MER	1.325	1.138	0.5	0.05	70	46.63	1	Flat
Microprobe	0.175	1.561	0.5	0.05	45			Sphere
MIRKA	0.5	2	-1	0	135	0	1	Flat
MSL	2.25	1.116	0.5	0.05	70	36.9, 59	0.5, 0.5	Flat
OREX	1.7	0.888	0.794	0	50	0, 75, 60	0.1, 0.7, 0.2	Flat
PAET	0.457	1.4	1	0	55			Ellipsoid
Pathfinder	1.325	1.066	0.5	0.05	70	49, 49	0.5, 0.5	Flat
Reentry-F	0.3965	10	0	0	5.7			Flat
Stardust	0.4135	1.347	0.5625	0.05	60	30, 30	0.5, 0.5	Flat
Venus_Pioneer_Probe	0.38	1.342	0.5	0	45	0, 90	0.3, -0.15	Ellipsoid
Venus_Pioneer_Sounder	0.71	1.465	0.5	0	45	90, 0, 90, 0, 60	-0.12, 0.37, -0.044, 0.08, 0.55	Flat
Viking	1.75	0.9381	0.5	0.015	70	39, 62.2	0.5076, 0.4924	Flat

## References

- <sup>1</sup> Lockwood, M.: "Neptune Aerocapture Systems Analysis," AIAA-2004-4951, August 2004.
- <sup>2</sup> Lockwood, M.: "Titan Aerocapture Systems Analysis," AIAA-2003-4799, July 2003.
- <sup>3</sup> Johns, B.; Fan, K.; Tveten, T.; Yeung, L.; Cheatwood, N.; and Qualls, G.: "Framework for Analysis and Collaborative Engineering (FACE)," AIAA 2002-0755, January 2002.
- <sup>4</sup> Allen, G. A.; Gage, P. J.; Venkatapathy, E.; Olynick, D. R.; and Wercinkski, P. F.: "A Web-based Analysis for Planetary Entry Vehicle Design," AIAA-98-4826, September 1998.
- <sup>5</sup> Papadopoulos, P. and Subrahmanyam, P.: "Web-Based Computational Investigation of Aerothermodynamics of Atmospheric Entry Vehicles," *Journal of Spacecraft and Rockets*, Vol. 43, No. 6, November-December 2006, pp. 1184–1190.
- <sup>6</sup> Alemany, K.; Wells, G.; Theisinger, J.; Clark, I.; and Braun, R.: "Mars Entry, Descent, and Landing Parametric Sizing and Design Space Visualization Trades," AIAA-2006-6022, August 2006.
- <sup>7</sup> Rogers, J. L.: "DeMAID – A Design Manager's Aid," NASA TM-101575, March 1989.
- <sup>8</sup> Hall, J.: "Mission Design and Systems Analysis for Ablative TPS Applications," Presented at JPL during Tutorial on Ablative TPS, August 2, 2005.
- <sup>9</sup> Justus, C. G. and Braun, R. D.: "Atmospheric Environments for Entry, Descent and Landing (EDL)," Fifth International Planetary Probe Workshop, Bordeaux, France, June 2007.  
<http://nssdc.gsfc.nasa.gov/planetary/factsheet/index.html>, Accessed February 05, 2009.
- <sup>10</sup> Justus, C. G.; Duvall, A.; and Keller, V. W.: "Atmospheric model for aerocapture Studies," AIAA-2004-4952, August 2004.
- <sup>11</sup> Justus, C. G.; Duvall, A.; Keller, V. W.; Spilker, T. R.; and Lockwood, M. K.: "Connecting Atmospheric Science and atmospheric Models for Aerocapture at Titan and the Other Planets," *Planetary and Space Science*, Vol. 53, 2005, pp. 601–605.

- <sup>12</sup> Muth, W. D.; Hoffmann, C.; and Lyne, J. E.: "Earth Return Aerocapture for the TransHab / Ellipsled Vehicle," NAG1-2163, October 2000
- <sup>13</sup> Edquist, K. T.; Prabhu, R.; Hoffman, D.; and Rea, J.: "Configuration Aerodynamics, and Stability Analysis for a Neptune Aerocapture Orbiter," AIAA-2004-4953, August 2004.
- <sup>14</sup> Regan, F. J. and Anandakrishnan, S. M.: *Dynamics of Atmospheric Re-Entry*. AIAA, Washington D. C., 1993.
- <sup>15</sup> Wilmoth, R. G.: "DACFREE—A Free-Molecular/Newtonian Code for Hypersonic Flow, A Users Guide," 1999.
- <sup>16</sup> Moss, J. N.; Wilmoth, R. G.; and Price, J. M.: "Direct Simulation Monte Carlo Calculations of Aerothermodynamics for Mars Microprobe Capsules," *Journal of Spacecraft and Rockets*, Vol. 36, No. 3, May-June 1999, pp. 399–404.
- <sup>17</sup> Moss, J. N.; Wilmoth, R. G.; and Price, J. M.: "Direct Simulation Monte Carlo Calculations of Aerothermodynamics for Mars Pathfinder and Mars Microprobe Capsules," AIAA-1997-2508, June 1997.
- <sup>18</sup> Hamilton, H. H.; Greene, F. A.; and DeJarnette, F. R.: "An Approximate Method for Calculating Heating Rates on Three-Dimensional Vehicles," AIAA-93-2881, July 1993.
- <sup>19</sup> Sutton, K. and Graves, R. A.: "A General Stagnation-Point Convective-Heating Equation for Arbitrary Gas Mixtures," NASA-TR-R-376, November 1971.
- <sup>20</sup> Tauber, M. E. and Sutton, K.: "Stagnation-Point Radiative Heating Relations for Earth and Mars Entries," *Journal of Spacecraft*, Vol. 28, No. 1, Jan-Feb 1991, pp. 40–42.
- <sup>21</sup> Mazaheri, A.: "Tool for Sphere-Cone Aerothermodynamic Analysis for Planetary Entry (TSCAAPE)," NASA-CR-2008-215346, August 2008.
- <sup>22</sup> Gnoffo, P.A.: "Users's Manual for the Langley Aerothermodynamic Upwind Relaxation Algorithm(LAURA)," NASA TM-4674, April 1996.
- <sup>23</sup> Brauer, G. L.; Cornick, D. E.; and Stevenson, R.: "Capabilities and Applications of the Program to Optimize Simulated Trajectories (POST)," NASA CR-2770, Feb. 1977.
- <sup>24</sup> Griffin, M. D. and French, J. R.: *Space Vehicle Design*. Second Edition, AIAA, 2004.
- <sup>25</sup> Press, W. H.; Teukolsky, S. A.; Vetterling, W. T.; and Flannery, B. P.: *Numerical Recipes in C*. Second Edition, Cambridge University Press, 1992.
- <sup>26</sup> Hall, J. L. and Lee, A. K.: "Aerocapture Trajectories for Spacecraft with Large Tow Ballutes," AAS/AIAA, AAS-01-235, Feb 2001.
- <sup>27</sup> Chen, Y.-K. and Milos, F. S., "Ablation and Thermal Response Program for Spacecraft Heatshield Analysis," *Journal of Spacecraft and Rockets*, Vol. 36, No. 3, 1999, pp. 475–483.
- <sup>28</sup> Davies, C. and Arcadi, M.: "Planetary Mission Entry Vehicles Quick Reference Guide: Version 3.0," NASA/SP-2006-3401, last updated December 12, 2007.

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p><b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</b></p>					
1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE		3. DATES COVERED (From - To)	
01-11-2009		Technical Memorandum			
4. TITLE AND SUBTITLE A Multidisciplinary Tool for Systems Analysis of Planetary Entry, Descent, and Landing (SAPE)				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Samareh, Jamshid A.				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER 346620.04.07.01.01.02	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) NASA Langley Research Center Hampton, VA 23681-2199				8. PERFORMING ORGANIZATION REPORT NUMBER  L-19730	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001				10. SPONSOR/MONITOR'S ACRONYM(S)  NASA	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) NASA/TM-2009-215950	
12. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Category -66 Systems Analysis and Operations Research Availability: NASA CASI (443) 757-5802					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT SAPE is a Python-based multidisciplinary tool for systems analysis of planetary entry, descent, and landing (EDL) for Venus, Earth, Mars, Jupiter, Saturn, Uranus, Neptune, and Titan. The tool is partially developed, and the goal is to provide a variable-fidelity capability for conceptual and preliminary analysis within the same framework. SAPE currently includes the following analysis modules: geometry, trajectory, aerodynamics, aerothermal, thermal protection system, and structural sizing. SAPE uses the Python language—a platform-independent open-source software—for integration and for the user interface. The development has relied heavily on the object-oriented programming capabilities that are available in Python. Modules are provided to interface with commercial and government off-the-shelf software components (e.g., thermal protection systems and finite-element analysis). SAPE currently runs on Microsoft Windows and Apple Mac OS X and has been partially tested on Linux.					
15. SUBJECT TERMS EDL; MDO; python; system analysis					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			STI Help Desk (email: help@sti.nasa.gov)
U	U	U	UU	21	19b. TELEPHONE NUMBER (include area code) (443) 757-5802